

A CABLE SEPARATOR SPLINE

See a' →
FIELD of the INVENTION

5 The present invention relates to a separator filler or spline.
More particularly the present invention relates to the separator filler or
spline having four pockets with each pocket having a cross-sectional
area that is less than the envelope area of a pair of cables adapted to
be placed in each pocket.

10

BACKGROUND of the INVENTION

 The most popular separator fillers or splines are generally
based on a circular cross-section wherein each pocket generally has a
15 cross-sectional area that is greater than the cross-sectional envelope
area of the twisted pair cable that is to be placed in the pocket. This
type of spline generally has less flexibility and undesirable to skew
degradation.

20 SUMMARY of the INVENTION

 The oval envelope provided by my spline has an acceptable
NEXT performance and good flexibility. Therefore, it is an object of the
present invention to provide a cable separator filler or spline having a
25 plurality and preferably four opened pockets for separating a plurality
of cable pairs, preferably one cable pair for each pocket. Preferably
when there are an even number of pockets, the pockets are
diametrically opposite each other. When there are four pockets, the
first and second pockets are diametrically opposite each other and
30 third and fourth pockets are diametrically opposite each other. In a
cross-sectional plane of the spline the diametric distance between the
ends of the first and second pockets is greater than the diametric

preserve its exterior shape, and substantially improve NEXT while still enhancing the attenuation delta and skew of pairs.

Generally alien NEXT is minimized since the cables "oval" will provide air spacing between parallel cables of any other type. Also there are economies in my spline over the generally used cylindrical splines in that less filler material generally is used in my elongated separator spline than in a round design for equal performance.

The present invention and the advantages thereof will become more apparent upon consideration of the following detailed description when taken in conjunction with the accompanying drawings

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a perspective view of the elongated separator spline of my invention.

FIGURE 2 is a cross-sectional view taken along lines 2-2 of FIGURE 1.

FIGURE 3 is the same as FIGURE 2 except having a shaded portion to define a cross-sectional area.

FIGURE 4 is a cross-section of a twisted pair cable to be used with the spline of FIGURE 1.

FIGURE 5 is perspective view of a cable utilizing my elongated separator spline.

FIGURE 6 is a cross-section view taken along lines 6-6 of FIGURE 5.

FIGURE 7 is a perspective view of another cable utilizing my elongated separator spline.

FIGURE 8 is a perspective view of still another cable utilizing my elongated separator spline.

FIGURE 9 is a perspective view of a further cable utilizing my elongated separator spline.

DETAILED DESCRIPTION

The following description taken in conjunction with the drawings will further explain the inventive features of my elongated separator spline and cables utilizing my elongated separator spline.

Referring to FIGURES 1 and 2, my elongated separator spline 20 has along its cross-sectional plane a major axis 21 and a minor axis 22. In the preferred embodiment, the minor axis 22 is perpendicular to the major axis 21. The preferred elongated separator spline 20 is shown with four cable pockets 23, 24, 26, and 27. Other oval configurations could have more all less pockets. The pockets 23 and 24 are on the major axis 21 and pockets 27 and 26 are on the minor axis 22. In a preferred embodiment, pockets 23 and 24 have the same cross-sectional area as each other and pockets 26 and 27 have the same cross-sectional area as each other. If desired, they can all have the same cross-sectional area. The cross-sectional area of the pockets as shown in FIGURE 3. These are indicated by the shaded areas 28 and 29.

FIGURE 4 illustrates a cross-section of a twisted pair cable 30 having a pair of conductors 35 with appropriate insulation 35(a). The cable 30 has a circular envelope 31. The cross-sectional area of the twisted pair circular envelope 31 is greater than the cross-sectional area of any of the pockets.

Each of the pockets 23 and 24 have a depth 32 and each of the pockets 26 and 27 have a depth 33. The depths 32 and 33 of the pockets is less than the diameter 34 of the twisted pair envelope 31. The cross-sectional depth 32 of the pockets 23 and 24 is less than the cross-sectional depth 33 of the pockets 26 and 27. In a preferred embodiment, each of the cross-sectional areas 28 and 29 is 25% to 75 % of the cross-sectional area of the envelope 31. The preferred elongated separator spline 20 has four longitudinally extending pockets 23, 24, 26 and 27 of two different sizes. However, if it is desired, the

09595613-001301
RECEIVED

The shield 51 is generally laterally wrapped around the core 44 and then the jacket 43 is extruded around the shield. Although the shield is shown as a lateral wrapped tape, it can be a helically wound tape. A drain wire (not shown) can be inserted into the cable 50 if desired.

5 Referring to FIGURE 8, there is shown a cable 60 using a drain wire 61. The cable 60 has the same construction as the cable 50 except in this embodiment of the drain wire 61 is helically wrapped around the lateral shield 51 for the dual purpose of being a drain wire and to hold the lateral shield 51 in place. The jacket 43 is then
10 extruded over the shield 51 and drain wire 61.

Referring to FIGURE 9, there is shown still another cable 70 having the same construction as the cable 50 except it uses a drain wire 71 having a gentle wrap around the lateral shield 51. The jacket 43 is then extruded over the shield 51 and drain wire 71.

15 The drain wires 61 and 71 are generally made with tinned copper, tinned aluminum, etc.

The size of the twisted pair cables 41 and 42 are generally about 24AWG. to about 22AWG.

The conductors 35 for the twisted pair cables are generally
20 copper, tinned copper, or an appropriate bronze and these are generally insulated with a foamed on non-foamed insulation 35(a) of polyethylene, polypropylene, fluorinated ethylene propylene, tetrafluoroethylene, polyvinyl chloride, etc.

Although I have described my elongated spline as having four
25 pockets, the spline may have more or less pockets.

It will, of course, be appreciated that the embodiments which have just been described have been given by way of illustration, and the invention is not limited to the precise embodiments described herein. Various changes and modifications may be effected by one
30 skilled in the art at without departing from the scope or spirit of the invention as defined in the appended claims.